





TC1 Palgrip® 1200 x 800 mm





Art.-Nr.: 87065899

Pal^{grip}

Technical data				
Dimensions L x W x H (mm)	1200 x 800 x 160			
Weight(kg)	19.0 kg			
Materia *²	PE			
Load capacity (kg)*3	Static 7500 kg	Dynamic 1250 kg	In Racking System 1000 kg	
Characteristics		Options		
Colour: grey/blue Runners: 3, unwelded		-		
Antislip: yes, Palgrip [®] -Anti-slip top deck Temperature stability: -30 °C to +40 °C, briefly up to +90 °C				
Loading quantities (Pcs / Approximate amount)				
Container	Container 20': 192 Container 40': 390	Container 40' Hig Conventional tra	h Cube: 440 iler 45' high cube container: 495	

Container	Container 20': 192 Container 40': 390	Container 40' High Cube: 440 Conventional trailer 45' high cube container: 495

MEGA-Trailer: 612 Jumbo: **684** Truck

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C.
 Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
 In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20 °C.